

```

<html dir="rtl">

<head>
<meta http-equiv="Content-Language" content="en-us">
<meta http-equiv="Content-Type" content="text/html; charset=windows-1252">
<title>&#1578;&#1575;&#1576;&#1608;&#1578; &#1607;&#1603;&#1585;</title>
<style>
<!--
.page {
    BACKGROUND: #0c0c0c; COLOR: #666666
}
.tborder {
    BACKGROUND: #0c0c0c; COLOR: #999999
}
TD {
    FONT: 10pt verdana, geneva, lucida, 'lucida grande', arial, helvetica, sans-serif
}
.alt1 {
    BACKGROUND: #0c0c0c url('http://www.sa-hacker.com/vb/images/x3-
s_/images/x3.png') repeat-x left top; COLOR: #cccccc
}
.navbar {
    FONT: 12px verdana, geneva, lucida, 'lucida grande', arial, helvetica, sans-serif
}
-->
</style>
<meta name="description" content="&#1578;&#1575;&#1576;&#1608;&#1578;
&#1607;&#1603;&#1585;">
</head>

<body bgcolor="#000000" link="#00FF00" text="#FFFFFF">

<div align="center">
    <table border="1" width="60%" bordercolorlight="#FFFFFF"
bordercolordark="#FFFFFF" bgcolor="#0C0C0C">
        <tr>

            <td align="center">
                <p align="center"><strong><font
size="5">&#1581;&#1600;&#1600;&#1605;&#1600;&#1600;&#1604;&#1600;&#1577;
&#1601;&#1600;&#1600;&#1585;&#1606;&#1600;&#1587;&#1600;&#1575;

                &#1575;&#1604;&#1575;&#1585;&#1587;&#1600;&#1600;&#1600;&#1608;&#160
4;&#1600;&#1600;&#1600; &#1575;&#1604;&#1604;&#1607; </font></strong></p>
                <p align="center">
                    <span id="result_box" lang="en" class="short_text" a="undefined"
closure_uid_tkvv4n="137" c="4" Tc="null">
                        <span class="hps" closure_uid_tkvv4n="378" Tc="null"><font
size="5">
                            Campaign</font></span></p>

```

Tc="null">against
to

the Messenger of Allah</p>
<p align="center">Hacked
By:TaBooT</p>
<p align="center">
</p>
<p align="center">

Si
Arafok <span class="hps
atn">d'Atbauk<span id="result_box3" class="short_text"
lang="en">
</p>
<p align="center">
<span
class="hps">Raisons
ne semble pas <span
class="hps">provoquer
le magazine de
Charlie

Prophète de
paix
soient sur lui a
supervisé la
création</p>
<p align="center">
<span id="result_box0" lang="en" class="short_text" a="undefined"
c="4" Tc="null" closure_uid_kq51kf="106">
<font
size="4">
Holy Quran</p>
<p align="center">
http://quran.muslim-web.com/</p>
<p align="center"><font
size="4">
http://www.tvquran.com/</p>
<p align="center">T<font
color="#00FF00">aBooT</p>
<p align="center">T<font
color="#00FF00">aBooT@HoT<font
color="#00FF00">mAiL.cO<font
color="#00FF00">m</td>

```

        </tr>
    </table>
</div>

</body>

</html>
<STYLE TYPE="text/css">
<!--
BODY {background-image: URL(http://i42.servimg.com/u/f42/16/52/07/59/kaba10.jpg);
background-position: center;
background-repeat: no-repeat;
background-attachment: fixed;}
-->
</STYLE>
</STYLE>
</script>
<embed src="http://www.abo-ali.com/mp3/Kllna_alqool_qool.mp3" width=0 height=0
border="0" type=audio/x-pn-realaudio-plugin true controls="ControlPanel,StatusBar"
autostart=True loop=0>

<body onbeforeprint="onbeforeprint()" onafterprint="onafterprint()"
onselectstart="return false" oncontextmenu="return false">

</body>

</html>

<script language="JavaScript1.2">

/*****
* Visit our site at http://www.star28.com/ for more code
* This notice must stay intact for use
*****/
//change 1 to another integer to alter the scroll speed. Greater is faster
var speed=1
var currentpos=0,alt=1,curpos1=0,curpos2=-1
function initialize(){
startit()
}
function scrollwindow(){
if (document.all)
temp=document.body.scrollTop
else
temp=window.pageYOffset
if (alt==0)
alt=1
else
alt=0
if (alt==0)

```

```
curpos1=temp
else
curpos2=temp
if (curpos1!=curpos2){
if (document.all)
currentpos=document.body.scrollTop+speed
else
currentpos=window.pageYOffset+speed
window.scroll(0,currentpos)
}
else{
currentpos=30
window.scroll(0,currentpos)
}
}
function startit(){
setInterval("scrollwindow()",30)
}
window.onload=initialize
</script>
```